

“I hereby declare that I have read this thesis and in my opinion this thesis is sufficient in terms of scope and quality for the award of the degree of Master of Science of Construction Management”

Signature :

Name of Supervisor : ASSOC. PROF. IR. DR. ROSLI MOHAMAD ZIN

Date : 16 NOVEMBER 2009

Signature :

Name of Co-Supervisor : ASSOC. PROF. BADERUL HISHAM BIN AHMAD

Date : 16 NOVEMBER 2009

CABLE STAYED BRIDGE CONSTRUCTION: CASE STUDY OF SUNGAI
JOHOR CABLE STAYED BRIDGE

LEE FOO WEI

A report submitted in partial fulfilment of the
requirements for the award of the degree of
Master of Science (Construction Management)

Faculty of Civil Engineering
Universiti Teknologi Malaysia

November 2009

I declare that this thesis entitled “CABLE STAYED BRIDGE CONSTRUCTION: CASE STUDY OF SUNGAI JOHOR CABLE STAYED BRIDGE” is the result of my own research except as cited in the references. The thesis has not been accepted for any degree and is not concurrently submitted in candidature of any other degree.

Signature :

Name : LEE FOO WEI

Date : 16 NOVEMBER 2009

To my beloved parents, siblings and friends for their never ending care and support.
Thank you for everything.

ACKNOWLEDGEMENT

Herewith, I would like to take this opportunity to express my gratefulness and acknowledgement to everyone that has given a helping hand throughout the whole process in thesis preparing.

First and foremost, to my dedicated supervisor of this research, Assoc. Prof. Ir. Dr. Rosli Mohamad Zin, and co-supervisor, Assoc. Prof. Dr. Haji Baderul Hisham Bin Ahmad, beyond measure of thanks I would like to say for the hearthen, guidance and assistance.

I would also like to acknowledge the guidance and assistance from all of the respondents and interviewees from Ranhill Engineers and Construction Sdn. Bhd and Lembaga Lebu Raya Malaysia, especially Mr. Muhammad Ridwan Goh and my partner Miss Madiyah, thank you so much for every cooperation and instruction given.

Last but not least, to my lovely parents and friends. I appreciate and enjoy the every moment with your all. Thank you for the support and love. You all have made me the best.

ABSTRACT

Cable-stayed bridges are becoming increasingly popular in the world. However, the lack of experience in cable-stayed bridge construction may lead to unsuccessful projects including cost overruns and schedule delays. In light of these potential problems, a need exists to document the methods of construction used in past cable-stayed bridge projects. This study documents the methods of construction of the Sungai Johor Cable-Stayed Bridge. Throughout the study, issues regarding construction problems and innovation are highlighted. This case study describes the general characteristics of the project, significant construction methods and techniques, and factors contributing to project success. Incremental launching, balanced cantilever, self-climbing formwork are typical important construction techniques been used in this case study. There are 24 problems been identified during the implementation of this cable stayed bridge. A questionnaire was developed to facilitate systematic data collection based on the factors grouped under four main project aspects, namely, project characteristics, contractual arrangements, project participants, and interactive processes. Experts who are involves in this construction industry were invited to participate in the survey. There are six critical success factors addressing budget performance, schedule performance, quality performance, and overall project success been identified with also some pertinent findings of the study are discussed.

ABSTRAK

Pembinaan jambatan kabel-penahan telah menjadi semakin popular dalam dunia. Walaubagaimanapun, kekurangan pengamalan dalam pembinaan jambatan kabel-penahan ini akan menyebabkan kegagalan projek termasuk melampaui kos dan penangguhan jadual pembinaan. Jadi, keperluan mendokumentasikan cara-cara pembinaan projek jambatan kabel-penahan berpandukan project lepas amat diperlukan untuk mengurangkan masalah bakal ini. Pengajian ini mendokumentasikan cara-cara pembinaan Jambatan Kabel-Penahan Sungai Johor. Melalui pengajian ini, isu-isu yang berkaitan dengan masalah pembinaan dan inovasi teknologi yang digunakan akan dipentingkan. Kes pengajian ini menguraikan ciri-ciri umum projek, cara-cara dan teknik-teknik pembinaan yang penting, serta faktor-faktor yang menyumbang kepada kejayaan projek ini. Pelancaran tokokan, penyokong seimbang, acuan mendaki diri adalah teknik-teknik pembinaan yang penting yang digunakan dalam kajian kes ini. Terdapat 24 masalah dihadapi semasa menjalankan kerja-kerja pembinaan jambatan kabel-penahan ini. Satu soal selidik telah dibangunkan untuk memudahkan pengumpulan data sistematik berdasarkan faktor-faktor yang dikategorikan dibawah empat aspek projek yang utama iaitu ciri-ciri projek, aturan bersifat kontrak, peserta projek dan proses interaktif. Bakal-bakal yang terlibat dalam pembinaan jambatan ini telah diajak untuk menjawab soal selidik ini. Terdapat enam faktor kejayaan yang kritikal dikenalpastikan dengan dikenali sebagai prestasi belanjawan, prestasi jadual pembinaan, prestasi kualiti dan keseluruhan kejayaan projek serta membincangkan juga beberapa penemuan-penemuan yang berkaitan dengan kajian ini.

TABLE OF CONTENTS

CHAPTER	TITLE	PAGE
	DECLARATION	ii
	DEDICATION	iii
	ACKNOWLEDGEMENTS	iv
	ABSTRACT	v
	ABSTRAK	vi
	ABSTRAK	vi
	TABLE OF CONTENTS	vii
	LIST OF TABLES	xiii
	LIST OF FIGURES	xiv
	LIST OF ABBREVIATIONS	xviii
	LIST OF APPENDICES	xix
1	INTRODUCTION	1
	1.1 General Overview	1
	1.2 Problem Statement	3
	1.3 Aim and Objectives of Study	4
	1.4 Scope of Study	5
	1.5 Methodology	6
	1.6 Summary of the Chapters	7
2	LITERATURE REVIEW	8
	2.1 Introduction	8
	2.2 Historical Review of Cable Stayed Bridge	9
	2.3 Two Cognitions Lead to Modern Cable Stayed Bridge	12
	2.4 Basic Bridge Types	12
	2.4.1 Girder Bridge	12

2.4.2	Truss Bridge	13
2.4.3	Rigid Frame Bridge	14
2.4.4	Arch Bridge	15
2.4.5	Cable Stayed Bridge	17
2.4.6	Suspension Bridge	19
2.5	Bridge Location	20
2.5.1	Introduction	20
2.5.2	Transportation Requirements	21
2.5.3	Technical Requirements	21
2.5.4	Aesthetic Considerations	22
2.6	Variations of Cable Stayed Bridge	22
2.6.1	Side-Spar Cable Stayed Bridge	22
2.6.2	Cantilever Spar Cable Stayed Bridge	23
2.6.3	Multiple Span Cable Stayed Bridge	24
2.6.4	Extradosed Bridge	25
2.6.5	Cable Stayed Cradle System Bridge	25
2.7	Basic Concept of Cable Stayed Bridge	26
2.7.1	Arrangement of the Stay Cables	26
2.7.1.1	Radial or Converging System	27
2.7.1.2	Harp or Parallel System	27
2.7.1.3	Fan or Intermediate System	28
2.7.1.4	Star System	28
2.7.2	Positions of the Cables in Space	28
2.7.2.1	Two Vertical Planes System	29
2.7.2.2	Two Inclined Planes System	30
2.7.2.3	Single Plane System	30
2.7.3	Types of Cables	31
2.7.4	Corrosion Protection	32
2.7.5	Anchorage of Cables	33
2.7.6	Tower Types	34
2.7.6.1	Tower Fixed at the Foundation	35
2.7.6.2	Tower Fixed at the Superstructure	36
2.7.6.3	Hinged Tower	36
2.7.7	Deck Types	36

2.7.8	Main Girders and Trusses	37
2.7.8.1	Steel Girders	37
2.7.8.2	Reinforced or Prestressed Concrete Girders	39
2.7.8.3	Trusses	40
2.7.9	Foundations	41
2.8	Erection of Cable Stayed Bridges	42
2.8.1	Construction on Scaffoldings or Temporary Supports	42
2.8.2	Construction by Rotation	44
2.8.3	Installation by Incremental Launching	47
2.8.4	Construction by Cantilever Method	49
2.8.5	Steel Composite Bridge Decks	52
2.8.6	Concrete Bridge Decks	53
2.8.7	Erection of Stay Cables	53
2.9	Comparison with Suspension Bridge	54
2.10	Case Study of Burlington Cable Stayed Bridge	56
2.10.1	Introduction	56
2.10.2	Construction Methods and Techniques	56
2.10.3	Sequence of Tower Construction	57
2.10.4	Formwork	58
2.10.5	Pouring Concrete	59
2.10.6	Local Off - Site Fabrication of Cables	59
2.10.7	Sequence for Placing Bridge Deck and Cables	60
2.10.8	Hanging Cables	61
2.10.9	Precast Deck Panels	62
2.10.10	Use of Tower Crane	63
2.11	Factors Contributing to Success of Burlington Cable Stayed Bridge	63
2.12	Project Challenges of Sutong Cable Stayed Bridge	66
2.13	Critical Success Factors for Cable Stayed Bridge	67
2.13.1	Introduction	67
2.13.2	Factors Related to Construction Project Success	68
2.13.3	Analytical Hierarchy Process	70
2.13.4	Hierarchy Model for Construction Project Success	71

3	METHODOLOGY	73
3.1	Introduction	73
3.2	Literature Review	73
3.2.1	Text Based Materials	74
3.2.2	Preliminary Interview and Site Visit	74
3.3	Document Study	74
3.4	Questionnaire Survey	74
3.4.1	Data Analysis and Establish a Framework of Critical Causes for Successful Implementation of Cable Stayed Bridge	75
3.4.2	Average Index	75
3.4.3	Establish of a Framework of Critical Factors	76
3.5	Interview with Client and Contractor	76
3.6	Secondary Data	77
3.7	Conclusion and Recommendation	77
4	RESULTS AND DISCUSSION	78
4.1	Introduction	78
4.2	Project Description	78
4.3	Foundation of Sungai Johor Cable Stayed Bridge	81
4.3.1	Foundation Construction	82
4.3.2	Pile Cap and Pier	82
4.4	Pylon	83
4.4.1	Pylon Construction	84
4.4.2	Lower Pylon Construction	84
4.4.3	Upper Pylon Construction	85
4.4.4	Pylon Construction Sequences	86
4.4.5	Summary of Pylon Construction	88
4.5	The Main Span Unit	88
4.5.1	Main Span Erection Method	89
4.6	The Side Span Unit	93
4.6.1	Side Span Erection Method	93
4.7	Segment Installation	96

4.8	Parallel Wire Strands	97
4.8.1	Strand Bundle	97
4.8.2	Tubing	98
4.8.3	Anchorage of the Cables	98
4.8.4	Deck-Stay Connection	99
4.8.5	Cables Construction	100
4.9	Construction Problems	101
4.9.1	Foundation Related Problems	101
4.9.2	Superstructure Related Problems	105
4.9.3	Pylon Related Problems	108
4.9.4	Materials Transportation Related Problems	111
4.9.5	Access Related Problems	111
4.9.6	Concreting Related Problems	112
4.9.7	Corrosion Related Problems	112
4.10	Results of Questionnaire Survey	112
4.10.1	Introduction	112
4.10.2	Based on Project Characteristics	113
4.10.3	Based on Contractual Arrangement	116
4.10.4	Based on Project Participants	118
4.10.5	Based on Interactive Process	125
4.10.6	Framework of Critical Success Factors in Implementation Cable Stayed Bridge	130
4.10.6.1	Ranked Order of Critical Factors by Contractors	130
4.10.6.2	Ranked Order of Critical Factors by Clients	132
4.10.6.3	Ranked Order of Critical Factors by Contractors and Clients	134
5	CONCLUSIONS AND RECOMMENDATIONS	136
5.1	Conclusion	136
5.2	Recommendation for Future Study	138

REFERENCES

139

APPENDICES A-B

145

LIST OF TABLES

TABLE NO.	TITLE	PAGE
2.1	Span ranking of cable stayed bridges (span >500m)	11
2.2	Elements of project success	66
2.3	Success – related factors considered in present study	69
2.4	Pairwise comparison scale	70
4.1	Facts and figures of Sungai Johor Cable Stayed Bridge	80
4.2	Detailing of Sungai Johor Cable Stayed Bridge	81
4.3	Response to project characteristics from contractors	114
4.4	Ranked important of project characteristics by contractors	115
4.5	Response to project characteristics from clients	115
4.6	Ranked important of project characteristics by clients	116
4.7	Response to contractual arrangement from contractors	117
4.8	Ranked important of contractual arrangement by contractors	117
4.9	Response to contractual arrangement from clients	118
4.10	Ranked important of contractual arrangement by clients	118
4.11	Response to project participants from contractors	119
4.12	Ranked important of project participants by contractors	121
4.13	Response to project participants from clients	122
4.14	Ranked important of project participants by clients	122
4.15	Response to interactive process from contractors	126
4.16	Ranked important of interactive process by contractors	127
4.17	Response to interactive process from clients	128
4.18	Ranked important of interactive process by clients	129
4.19	Ranked order of critical factors by contractors	131
4.20	Ranked order of critical factors by clients	133
4.21	Ranked order of critical factors by contractors and clients	135

LIST OF FIGURES

FIGURE NO.	TITLE	PAGE
1.1	Flow chart of Methodology	6
2.1	Egyptian sailing boat with rope –stayed sail beam.	9
2.2	Primitive bamboo bridge in Laos	9
2.3	(a) Steep fan shaped stays proposed by Poyet in 1821; (b) Flat harp shaped stays proposed by Hatley in 1840	10
2.4	Roebblings bridge at Niagara Falls.	10
2.5	(a) I-Beam Cross Section; (b) Box-Girder Cross Section	13
2.6	(a) Warren Truss; (b) Pratt Truss; (c) Howe Truss	14
2.7	(a) Batter Post Rigid Frame; (b) Pi Shaped Rigid Frame; (c) V shaped frame	15
2.8	(a) Hinge-Less Arch; (b) Two Hinged Arch; (c) Three-Hinged Arch; (d) Tied Arch	17
2.9	(a) Single Tower; (b) Double Tower; (c) portal Tower; (d) A-Shaped Tower	18
2.10	Cable Arrangements	19
2.11	(a) Typical Suspension Bridge; (b) Position of Saddle	20
2.12	Esplanade Riel in Winnipeg, Manitoba, Canada	23
2.13	Sundial Bridge at Turtle Bay	24
2.14	The Millau Viaduct in France is the world's highest bridge.	24
2.15	Octavio Frias de Oliveira Bridge, in São Paulo, Brazil	25
2.16	Placement of final pair of segments Veteran’s Glass City Skyway, Toledo, Ohio	26
2.17	Systems of cable arrangement	27

2.18	Space positions of cables (a) two vertical planes system; (b) two inclined planes system; (c) single plane system; (d) asymmetrical plane system	29
2.19	Helically-wound, parallel wire and locked coil cable strands	31
2.20	Devices for cable anchorages at the tower	33
2.21	Devices for cable anchorage at the deck	34
2.22	Tower types	35
2.23	Rib types (a) Torsionally weak or open type; (b) Torsionally stiff or box type.	37
2.24	Types of main girder	39
2.25	Reinforced and prestressed concrete girders	40
2.26	Reinforced and prestressed concrete girders	41
2.27	A pioneer concrete cable stayed bridge: the bridge which crosses the canal de Donzère Mondragon	43
2.28	Construction of the Lixhe Bridge: the steel structure has been installed on temporary supports; the pylons have been concreted, and the top slab is being built	44
2.29	Rotation of the second cantilever of the Meylan pedestrian bridge	45
2.30	Rotation of the unique cantilever of the Illhof pedestrian bridge	46
2.31	Rotation of the Ben Ahin Bridge, over the River Meuse, the cantilever is extended with the help of temporary pylon and the cables	46
2.32	(a) and (b) construction of the Seyssel Bridge. The steel structure is launched from the left bank with temporary pylon and cables; the remaining part from the right bank with a launching nose, a temporary support and a rear counterweight	48
2.33	(a) and (b) erection of the main span of the Saint- Nazaire Bridge. The successive segments are placed on a barge, and lifted from the deck by amobile derrick, progressing segment after segment on the cantilever	51
2.34	Erection of precast element of the cable stayed bridge over the Rio Ebro, built by the progressive cantilever method	52
2.35	(a) erection of precast deck panels after steel structure; (b) erection of complete segments	52

2.36	(a) Erection of stay cables with auxiliary cable; (b) Erection of stay cables without auxiliary cable; (c) Erection of stay cables with cable crane	54
2.37	Difference between Cable Stayed Bridge and Suspended Bridge	55
2.38	Concrete forming sequence for bridge tower construction. (a) end of previous pour; (b) place inside forms; (c) set rebar cage; (d) removal vertical strips and jump forms	57
2.39	Bridge deck construction sequence; (a) steel lifted into place; (b) cables hung and partially stresses, precast panels set, leveling screws adjusted; (c) tensioning bars coupled to previous segment, joints poured and slabs posttensioned	61
2.40	Typical construction project environment	72
2.41	Hierarchy model for construction project success	72
4.1	Elevation plan of Sungai Johor Cable Stayed Bridge	79
4.2	(a) Piles installation; (b) pile cap installation	83
4.3	Details of pylon	84
4.4	Construction sequences of main pylon	88
4.5	Typical cross section of main span unit	89
4.6	Typical balanced cantilever construction method	90
4.7	Balanced cantilever sequences	91
4.8	General arrangement of concrete deck	93
4.9	Type of sliding equipment used	94
4.10	Incremental launching sequences	95
4.11	Combination of concrete deck and composite deck	97
4.12	Anchorage of the cable at the top of pylon	99
4.13	Site located in rural and remote area	102
4.14	Mangrove swamp conditions	102
4.15	The crane barge and the tug boat are exposed to sea water potential lead to breaks down	103
4.16	Miss installation of piles	104
4.17	The PFA cement used on the surface and in the lower layer of pile cap and	104
4.18	The probe used to reinforce the weak pier columns	105
4.19	The precast slab is need to store before they can be laid	

	on the deck	106
4.20	Honeycomb and crack presented during concreting	107
4.21	The temporary probe is used before the lower cross beam is erected	108
4.22	The hammerhead tower crane and six probes installed during pylon construction	109
4.23	Installation of hydraulic cylinder to avoid sliding or overturning	110
4.24	The anchorage box	110
4.25	Framework of critical success factors ranked by contractors	132
4.26	Framework of critical success factors ranked by clients	134
4.27	Framework of critical success factors ranked by contractors and clients	135

LIST OF ABBREVIATIONS

AHP	Analytical Hierarchy Process
ASCE	American Society of Civil Engineering
BORR	Butterworth Outer Ring Road
CSFs	Critical Success Factors
FHWA	Federal Highway Administration
GPS	Global Positioning System
LLM	Lembaga Lebuhraya Malaysia
OPC	Ordinary Portland Cement
PC	Prestressed Concrete
PE	Polyethylene Pipe
PFA	Pulverised Fuel Ash
PRS	Pollutant Removal System
SDE	Senai Desaru Expressway
SDEB	Senai Desaru Expressway Berhad

LIST OF APPENDICES

APPENDIX	TITLE	PAGE
A	Site Visits Pictures	145
B	Questionnaire Form	147

CHAPTER I

INTRODUCTION

1.1 General Overview

Formerly, the only gateway to Desaru is Johor Bahru – Kota Tinggi Highway or Pengerang Highway which consume around 2 hours for typical journey. Nowadays, there is a new expressway (Senai – Desaru Expressway, SDE) which connects Senai in western Johor to Desaru in eastern Johor. It is part of the Iskandar Development Region with a total length of 77km (47.8 miles) constructed at an estimated cost of RM1.46bn. It is also expected to shorten the journey time from 2 hours to 45 minutes which helps to save a lot of money, time and economize the scarce of energy resources.

This tolled expressway will be a four – lane dual carriageway which will be able to improve road connection between western and eastern Johor. The road will start at Senai and link to the following places: Setia Indah, Taman Daya, Ulu Tiram, Pasir Gudang, Bandar Penawar and finally Desaru. It will be an alternative way to Desaru Beach, instead of Federal Route and be the main access road to Desaru from North – South Expressway Route and major road link to Senai International Airport from Kota Tinggi. The road will include four toll plazas and six interchanges, 1 intersection and 2 rest and service areas.

There are two phases for construction of this expressway. The first one is the road from Senai to Pasir Gudang whereas phase two of this project, the concerned one is involving the cable stayed 1708m long sungai bridge across the Johor River. It is soon to chalk up a milestone success in the engineering, operation and maintenance and expected to become a major landmark of Johor and become one of the longest single (central) plane cable – stayed bridges in Malaysia after Raja Pemasuri Bainun Bridge in Perak. This expressway project is also the third largest highway concession awarded by the Malaysian Government.

A cable-stayed bridge is a bridge that consists of one or more columns (normally referred to as towers or pylons), with cables supporting the bridge deck. There are two major classes of cable-stayed bridges: In a harp design, the cables are made nearly parallel by attaching cables to various points on the tower(s) so that the height of attachment of each cable on the tower is similar to the distance from the tower along the roadway to its lower attachment. In a fan design, the cables all connect to or pass over the top of the tower(s).

This bridge is designed in a harp configuration but in a single central plane (only one set of stay cables) which means that the cables are in near – parallel arrangement, having the merit of cables are attached to various points on each of the two “A” shaped concrete pylon towers. Each tower has a foundation of 34 – bore 2m – diameter steel cased piles. As a result, the distance from the tower along the roadway to its lower attachment is similar to the height of attachment if each cable on the tower.

The total length of this landmark bridge is about 1.7 km long while the main span of the bridge is 500m and the pylon height is 142.5m from the surface of the river. The middle 739m of the bridge has a composite deck with a 250mm thick precast concrete deck slab and a closed structural steel skirt (3.5m deep). There are two 484.5m deck sections on either side of the central section and these consist of a concrete box girder structure.

This SDE is the only one expressway in Malaysia which implements the Pollutant Removal System (PRS) to monitor and control any potential of a spillage of perilous and hazardous chemicals from any vehicle travelling on the expressway because it traverses through the environmentally sensitive water catchment area of Layang Reservoir.

1.2 Problem Statement

Johor is one of the popular destinations for tourists from other counties because of its southward region location in Malaysia. Due to Senai International Airport and Johor Bahru city such a strategic location in the background is connected to Singapore, many passengers are attracted to this region and aid the economy. However, if we probe into Johor's road infrastructure aspect, it is in need of severe improvement. The typical journey time from one place to another place sometimes took a long time.

Senai – Desaru Expressway is one of the endeavors from government to upgrade the Johor's road infrastructure. The construction works for this project is both technically and environmentally challenging especially the cable – stayed bridge. As cable- stayed bridges are becoming increasingly popular in Malaysia. The European community has viewed cable –stayed bridges to be the most advantageous, economical long span bridge since the end of World War II (Rowings and Kaspar, 1991).

Cable – stayed bridges may present a few different alternatives for the cable system. At least harp, fan or modified fan arrangements can be discussed at the beginning of the design (Walther, 1999). Cable – stayed bridges are designed to support load efficiently with all members carrying only axial forces (Rowings and Kaspar, 1991). They typically require less material than conventional bridges and rely on free cantilevered construction methods such that extensive falsework is not necessary.

Problems will occur that were not originally anticipated with the advent and implementation of any new technique or procedure. Contractual and technical problems are more frequent and threaten to stagnate the growth of the cable stayed bridge industry. Projects are completed over budget. Major difficulties occur, forcing significant completion delays. These kinds of projects have experienced major claims and litigation. In some cases, designers or contractors, or both have been terminated. Solutions to these problems must be sought in order to realize the technical and economic advantages offered by cable stayed bridge design.

However, aside from the design advantages, the lack of experience with cable –stayed bridges has posed many challenges to both owner and contractor project participants resulting in cost overrun, and scheduled delays which have to lead major claims, litigation, and termination of contractor and/or designers as seen on past cable –stayed bridges projects (Podolny and Scalzi, 1986). In addition, different challenges existed and critical factors for implementation of cable stayed bridge would be different or beyond if compared to other types of bridges. Therefore, a need exists to document the method of construction used on previously completed cable – stayed bridge projects. The lessons learned from one project, whether they are successful, failures or encounter difficulties, can assist in achieving success on future projects. Otherwise, people just repeat past failures only.

1.3 Aim and Objectives of Study

The aim of this project is to investigate and explore implementation and construction methods of cable stayed bridge in order to maximize its advantageous use and reduce the problems faced in the future. In accordance to, the specific objectives for the study are to be determined are:

- i) To study and document the methods of constructing cable stayed bridge.
- ii) To identify the problems faced by project participators during implementation of cable stayed bridge.
- iii) To establish a frame work of successfully factors for implementation and management of cable stayed bridge project.

1.4 Scope of Study

This study aims to evaluate the construction method, problems faced and critical factors for successfully implementation of cable stayed bridge. In order to accomplish the objectives, the following tasks are carried as:

- i) A through literature review based on the previous research works done.
- ii) Site visit and interview with client, contractor and consultant are the main process in this study.

This study only focus on cable stayed bridge construction, mainly on problems, construction method statements and critical factors for implementation of cable stayed bridge in order for a better understanding and assisting in future works. Structural analysis and stability is beyond the scope of this study. Some of the information and data can be collect from library, journals and books. However, the outcome of this study cannot represent the situation of all construction processes in SDE cable stayed bridge.

1.5 Methodology

The study will be carry out in two distinct stages. A flowchart of methodology of the study is shown in Figure 1.1. Details descriptions of the methodology are given in Chapter 3.




Figure 1.1: Flow chart of Methodology

1.6 Summary of the Chapters

This project paper is divided into six (6) chapters.

Chapter 1 describes the overall intention of the study. It also explains the objectives, the scope and limitation and the brief methodology adopted for the study.

Chapter 2 is a literature review on the cable stayed bridge. It describes historical development of cable stayed bridge, the types of bridge, and the basic concept and construction methods of cable stayed bridge.

Chapter 3 describes in detail the methodologies of study to achieve the objectives. This includes methodology for data collection and data analysis for site visit and interview with expert panels.

Chapter 4 analysis the data obtained from site visit and expert panels.

Chapter 5 discuss in details the data analysed in the previous chapter and present the findings for each of the results.

Chapter 6 concludes the overall study on the subject and evaluate whether the objectives of the study are met. Recommendations for future studies are also suggested.